



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification: G06F 13/00, G06F 15/16	A1	(11) International Publication Number: WO 00/16205 (43) International Publication Date: 23 March 2000 (23.03.2000)
--	-----------	--

(21) International Application Number: PCT/US99/20963 (22) International Filing Date: 09 September 1999 (09.09.1999) (30) Priority Data: 09/151,530 11 September 1998 (11.09.1998) US (60) Parent Application or Grant DIGITALCONVERGENCE.COM INC. [/]; (). PHILYAW, Jeffry, Jovan [/]; (). MATHEWS, David, Kent [/]; (). SMITH, Brad, Maxwell [/]; (). ADAMS, Paul, Scovell [/]; (). HOWISON, Gregory, M. ; ().	Published
--	-----------

- (54) Title: METHOD FOR CONTROLLING A COMPUTER WITH AN AUDIO SIGNAL.
(54) Titre: PROCEDE DE COMMANDE D'UN ORDINATEUR A L'AIDE D'UN SIGNAL AUDIO

(57) Abstract

A method for controlling a computer (302) by inputting an analog signal (111) into the computer (302) to control a web browser software application. The analog signal (111) contains a trigger signal which activates proprietary software, and a product identifier. The proprietary software launches the web browser application on the computer (302), extracts the product identifier, and creates an appended data string by appending server address (URL) routing information to the product identifier information. The appended data string is automatically inserted into the web browser as keystroke data and routed to an advertiser reference server (308). The appended routing information directs communication to the advertiser reference server (308) which contains a cross-referenced database (310) of advertiser product identifier information and associated advertiser server URLs. The advertiser server URL and a request for product information relevant to the product identifier is returned to the computer (302) web browser where it is automatically redirected to the advertiser server (312) containing the advertiser product information. The advertiser product information is then returned to the computer (302) for display.

(57) Abrégé

La présente invention concerne un procédé de commande d'un ordinateur (302) par entrée d'un signal analogique (111) dans l'ordinateur (302) afin de commander une application de programme de navigateur Web. Le signal analogique (111) contient un signal déclencheur qui active le logiciel breveté et un identificateur de produit. Le logiciel breveté lance, sur l'ordinateur (302), l'application de navigateur Web, extrait l'identificateur de produit, et crée une chaîne de données jointes en ajoutant une information d'acheminement d'adresse de serveur (URL) à l'information d'identificateur de produit. Cette chaîne de données jointes est automatiquement insérée dans le navigateur Web comme données de frappe et acheminée à un serveur de référence d'annonceur (308). L'information d'acheminement jointe dirige une communication vers le serveur de référence d'annonceur (308) qui contient une base de données d'équivalences (310) d'information d'identificateur de produit d'annonceur et d'adresses URL de serveur d'annonceur associé. L'adresse URL de serveur d'annonceur et une demande d'information de produit relative à l'identificateur de produit est renvoyée au navigateur Web de l'ordinateur (302), où elle est automatiquement dirigée de nouveau vers le serveur d'annonceur (312) qui contient l'information de produit d'annonceur. L'information de produit d'annonceur est alors renvoyée à l'ordinateur (302) pour affichage.

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 : G06F 13/00, 15/16		(11) International Publication Number: WO 00/16205
A1		(43) International Publication Date: 23 March 2000 (23.03.00)
<p>(21) International Application Number: PCT/US99/20963</p> <p>(22) International Filing Date: 9 September 1999 (09.09.99)</p> <p>(30) Priority Data: 09/151,530 11 September 1998 (11.09.98) US</p> <p>(71) Applicant: DIGITALCONVERGENCE.COM INC. [US/US]; 4264 Kellway Circle, Addison, TX 75244 (US).</p> <p>(72) Inventors: PHILYAW, Jeffry, Jovan; 5968 West Northwest Highway, No. 1813, Dallas, TX 75225 (US). MATHEWS, David, Kent; 3438 Livingston Lane, Carrollton, TX 75007 (US). SMITH, Brad, Maxwell; 4016 Hackmore Loop, Irving, TX 75061 (US). ADAMS, Paul, Scovell; 7419 Gracefield Lane, Dallas, TX 75248 (US).</p> <p>(74) Agent: HOWISON, Gregory, M.; Thompson & Howison, L.L.P., P.O. Box 741715, Dallas, TX 75374-1715 (US).</p> <p>(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).</p> <p>Published With international search report.</p>		
<p>(54) Title: METHOD FOR CONTROLLING A COMPUTER WITH AN AUDIO SIGNAL</p> <p>(57) Abstract</p> <p>A method for controlling a computer (302) by inputting an analog signal (111) into the computer (302) to control a web browser software application. The analog signal (111) contains a trigger signal which activates proprietary software, and a product identifier. The proprietary software launches the web browser application on the computer (302), extracts the product identifier, and creates an appended data string by appending server address (URL) routing information to the product identifier information. The appended data string is automatically inserted into the web browser as keystroke data and routed to an advertiser reference server (308). The appended routing information directs communication to the advertiser reference server URLs. The advertiser server URL and a request for product information relevant to the product identifier is returned to the computer (302) web browser where it is automatically redirected to the advertiser server (312) containing the advertiser product information. The advertiser product information is then returned to the computer (302) for display.</p>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

THIS PAGE BLANK (USPTO)

Description

5

10

15

20

25

30

35

40

45

50

55

5

**METHOD FOR CONTROLLING A COMPUTER
WITH AN AUDIO SIGNAL**

10

15

TECHNICAL FIELD OF THE INVENTION

20

This invention is related to a method of computer control, and particularly for automatically directing a web browser application on the computer to retrieve and display information in response to an analog signal.

25

CROSS REFERENCE TO RELATED APPLICATION

30

This application is related to copending U.S. Patent Application Serial No. 09/151,471, entitled, "METHOD FOR INTERFACING SCANNED PRODUCT INFORMATION WITH A SOURCE FOR THE PRODUCT OVER A GLOBAL NETWORK" (Atty Dkt No. PHLY-

5 24,397) filed of even date herewith.

35

40

45

50

55

BACKGROUND OF THE INVENTION

With the growing numbers of computer users connecting to the "Internet," many companies are seeking the substantial commercial opportunities presented by such a large user base. For example, one technology which exists allows a television ("TV") signal to trigger a computer response in which the consumer will be guided to a personalized web page. The source of the triggering signal may be a TV, video tape recorder, or radio. For example, if a viewer is watching a TV program in which an advertiser offers viewer voting, the advertiser may transmit a unique signal within the television signal which controls a program known as a "browser" on the viewer's computer to automatically display the advertiser's web page. The viewer then simply makes a selection which is then transmitted back to the advertiser.

In order to provide the viewer with the capability of responding to a wide variety of companies using this technology, a database of company information and Uniform Resource Locator ("URL") codes is necessarily maintained in the viewer's computer, requiring continuous updates. URLs are short strings of data that identify resources on the Internet: documents, images, downloadable files, services, electronic mailboxes, and other resources. URLs make resources available under a variety of naming schemes and access methods such as HTTP, FTP, and Internet mail, addressable in the same simple way. URLs reduce the tedium of "login to this server, then issue this magic command ..." down to a single click. The Internet uses URLs to specify the location of files on other servers. A URL includes the type of resource being accessed (e.g., Web, gopher, FTP), the address of the server, and the location of the file. The URL can point to any file on any networked computer. Current technology requires the viewer to perform periodic updates to obtain the most current URL database. This aspect of the current technology is cumbersome since the update process requires downloading information to the viewer's computer. Moreover, the likelihood for error in performing the update, and the necessity of redoing the update in the event of a later computer crash, further complicates the process. Additionally, current technologies are limited in the number of companies which may be stored in the database. This is a significant limitation since world-wide access presented by the Internet and the increasing number of companies connecting to perform on-line commerce necessitates a large database.

5

SUMMARY OF THE INVENTION

10

The present invention disclosed and claimed herein comprises a method for retrieving information from a storage region having a defined location. A program is broadcasted having embedded therein a routing signal having routing information contained therein. The routing

5 signal is then extracted from the broadcast. Thereafter, a personal computer is controlled to allow a user to retrieve the information from a storage region at the defined location, which defined

15 location is located with the extracted routing information, providing it at the personal computer for use by the user.

20

25

30

35

40

45

50

55

BRIEF DESCRIPTION OF THE DRAWINGS

For a more complete understanding of the present invention and the advantages thereof, reference is now made to the following description taken in conjunction with the accompanying Drawings in which:

FIGURE 1 illustrates a block diagram of the preferred embodiment;
FIGURE 2 illustrates the computer components employed in this embodiment;
FIGURE 3 illustrates system interactions over a global network;
FIGURES 4a-4e illustrate the various message packets transmitted between the source PC and network servers used in the preferred embodiment; and
FIGURE 5 is a flowchart depicting operation of the system according to the preferred embodiment.
FIGURE 6 illustrates a flowchart of actions taken by the Advertiser Reference Server ("ARS") server;
FIGURE 7 illustrates a flowchart of the interactive process between the source computer and ARS;
FIGURE 8 illustrates a web browser page receiving the modified URL/advertiser product data according to the preferred embodiment;
FIGURE 9 illustrates a simplified block diagram of the disclosed embodiment;
FIGURE 10 illustrates a more detailed, simplified block diagram of the embodiment of FIGURE 9;
FIGURE 11 illustrates a diagrammatic view of a method for performing the routing operation;
FIGURE 12 illustrates a block diagram of an alternate embodiment utilizing an optical region in the video image for generating the routing information;
FIGURE 13 illustrates a block diagram illustrating the generation of a profile with the disclosed embodiment;
FIGURE 14 illustrates a flowchart for generating the profile and storing at the ARS; and
FIGURE 15 illustrates a flowchart for processing the profile information when information is routed to a user.

5

DETAILED DESCRIPTION OF THE INVENTION

10

15

20

25

30

Referring now to FIGURE 1, there is illustrated a block diagram of a system for controlling a personal computer ("PC") 112 via an audio tone transmitted over a wireless system utilizing a TV. In the embodiment illustrated in FIGURE 1, there is provided a transmission station 101 and a receive station 117 that are connected via a communication link 108. The transmission station 101 is comprised of a television program source 104, which is operable to generate a program in the form of a broadcast signal comprised of video and audio. This is transmitted via conventional techniques along channels in the appropriate frequencies. The program source is input to a mixing device 106, which mixing device is operable to mix in an audio signal. This audio signal is derived from an audio source 100 which comprises a coded audio signal which is then modulated onto a carrier which is combined with the television program source 104. This signal combining can be done at the audio level, or it can even be done at the RF level in the form of a different carrier. However, the preferred method is to merely sum the audio signal from the modulator 102 into the audio channel of the program that is generated by the television program source 104. The output thereof is provided from the mixing device 106 in the form of broadcast signal to an antenna 107, which transmits the information over the communication link 108 to an antenna 109 on the receive side.

35

20

40

25

45

50

55

On the receive side of the system, a conventional receiver 110, such as a television is provided. This television provides a speaker output which provides the user with an audible signal. This is typically associated with the program. However, the receiver 110 in the disclosed embodiment, also provides an audio output jack, this being the type RCA jack. This jack is utilized to provide an audio output signal on a line 113 which is represented by an audio signal 111. This line 113 provides all of the audio that is received over the communication link 108 to the PC 112 in the audio input port on the PC 112. However, it should be understood that, although a direct connection is illustrated from the receiver 110 to the PC 112, there actually could be a microphone pickup at the PC 112 which could pick the audio signal up. In the disclosed embodiment the audio signal generated by the advertiser data input device 100 is audible to the human ear and, therefore, can be heard by the user. Therefore, no special filters are needed to provide this audio to the PC 112.

5 The PC 112 is operable to run programs thereon which typically are stored in a program
file area 116. These programs can be any type of programs such as word processing programs,
application programs, etc. In the disclosed embodiment, the program that is utilized in the
10 system is what is referred to as a "browser." The PC 112 runs a browser program to facilitate
5 the access of information on the network, for example, a global communication network known
as the "Internet" or the World-Wide-Web ("Web"). The browser is a hypertext-linked
15 application used for accessing information. Hypertext is a term used to describe a particular
organization of information within a data processing system, and its presentation to a user. It
exploits the computer's ability to link together information from a wide variety of sources to
20 provide the user with the ability to explore a particular topic. The traditional style of presentation
used in books employs an organization of the information which is imposed upon it by
limitations of the medium, namely fixed sized, sequential paper pages. Hypertext systems,
however, use a large number of units of text or other types of data such as image information,
25 graphical information, video information, or sound information, which can vary in size. A
collection of such units of information is termed a hypertext document, or where the hypertext
documents employ information other than text, hypermedia documents. Multimedia
30 communications may use the Hypertext Transfer Protocol ("HTTP"), and files or formatted data
may use the Hypertext Markup Language ("HTML"). This formatting language provides for a
mingling of text, graphics, sound, video, and hypertext links by "tagging" a text document using
20 HTML. Data encoded using HTML is often referred to as an "HTML document," an "HTML
page," or a "home page." These documents and other Internet resources may be accessed across
35 the network by means of a network addressing scheme which uses a locator referred to as a
Uniform Resource Locator ("URL"), for example, "http://www.digital.com."

40 The Internet is one of the most utilized networks for interconnecting distributed computer
25 systems and allows users of these computer systems to exchange data all over the world.
Connected to the Internet are many private networks, for example, corporate or commercial
45 networks. Standard protocols, such as the Transport Control Protocol ("TCP") and the Internet
Protocol ("IP") provide a convenient method for communicating across these diverse networks.
These protocols dictate how data are formatted and communicated. As a characteristic of the
50 Internet, the protocols are layered in an IP stack. At higher levels of the IP stack, such as the
30 application layer (where HTTP is employed), the user information is more readily visible, while

5 at lower levels, such as the network level (where TCP/IP are used), the data can merely be
observed as packets or a stream of rapidly moving digital signals. Superimposed on the Internet
10 is a standard protocol interface for accessing Web resources, such servers, files, Web pages, mail
messages, and the like. One way that Web resources can be accessed is by browsers made by
5 *Netscape®* and *Microsoft Internet Explorer®*.

15 Referring again now to FIGURE 1, the user can load this program with the appropriate
keystrokes such that a browser window will be displayed on a display 118. In one embodiment,
the user can run the browser program on the PC 112 such that the browser window is displayed
20 on the display 118. While watching a preferred program, the user can also view display 118.
10 When an audio signal is received by the receiver 110 and the encoded information is contained
therein that was input thereto by the advertiser, the PC 112 will then perform a number of
operations. The first operation, according to the disclosed embodiment, is to extract the audio
25 information within the received audio signal in the form of digital data, and then transmit this
digital data to a defined location on the global communication network via a modem connection
15 114. This connection will be described hereinbelow. This information will be relayed to a
proprietary location and the instructions sent back to the PC 112 as to the location of the
30 advertiser associated with the code, and the PC 112 will then effect a communication link to that
location such that the user can view on the display 118 information that the advertiser, by the fact
of putting the tone onto the broadcast channel, desires the viewer to view. This information can
35 20 be in the form of interactive programs, data files, etc. In one example, when an advertisement
appears on the television, the tone can be generated and then additional data displayed on the
display 118. Additionally, a streaming video program could be played on the PC received over
40 the network, which streaming video program is actually longer than the advertising segment on
the broadcast. Another example would be a sports game that would broadcast the tone in order to
25 allow a user access to information that is not available over the broadcast network, such as
additional statistics associated with the sports program, etc.

45 By utilizing the system described herein with respect to the disclosed embodiment of
FIGURE 1, an advertiser is allowed the ability to control a user's PC 112 through the use of tones
50 embedded within a program audio signal. As will be described hereinbelow, the disclosed
30 embodiment utilizes particular routing information stored in the PC 112 which allows the

5 encoded information in the received audio signal to route this information to a desired location on the network and then allow other routing information to be returned to the PC 112 for control thereof to route the PC 112 to the appropriate location associated with that code.

10 Referring now to FIGURE 2, there is illustrated a computer 204, similar to computer 112, connected to display information on display 118. The computer 204 comprises an internal audio or "sound" card 206 for receiving the transmitted audio signal through receive antenna 109 and receiver 110. The sound card 206 typically contains analog-to-digital circuitry for converting the analog audio signal into a digital signal. The digital signal may then be more easily manipulated by software programs. The receiver 110 separates the audio signal from the video signal. A special trigger signal located within the transmitted advertiser audio signal triggers proprietary software running on the computer 204 which launches a communication application, in this particular embodiment, the web browser application located on the PC 204. Coded advertiser information contained within the audio signal is then extracted and appended with the address of a proprietary server located on the communication network. The remote server address is in the form of a URL. This appended data, in addition to other control codes, is inserted directly into the web browser application for automatic routing to the communication network. The web browser running on PC 204, and communicating to the network with a through an internal modem 208, in this embodiment, transmits the advertiser information to the remote server. The remote server cross-references the advertiser product information to the address of the advertiser server located on the network. The address of the advertiser server is routed back through the PC 204 web browser to the advertiser server. The advertiser product information is returned to PC 204 to be presented to the viewer on display 118. In this particular embodiment, the particular advertiser product information displayed is contained within the advertiser's web page 212. As mentioned above, the audio signal is audible to the human ear. Therefore the audio signal, as emitted from the TV speakers, may be input to the sound card 206 via a microphone. Furthermore, the audio signal need not be a real-time broadcast, but may be on video tapes, CDs, DVD, or other media which may be displayed at a later date. With the imminent implementation of high definition digital television, the audio signal output from the TV may also be digital. Therefore, direct input into a sound card for A/D purposes may not be necessary, but alternative interfacing techniques to accommodate digital-to-digital signal formats would apply.

Referring now to FIGURE 3, there is illustrated a source PC 302, similar to PCs 204 and 112, connected to a global communication network 306 through an interface 304. In this embodiment, the audio signal 111 is received by PC 302 through its sound card 206. The audio signal 111 comprises a trigger signal which triggers proprietary software into launching a web browser application residing on the PC 302. The audio signal 111 also comprises advertiser product information which is extracted and appended with URL information of an Advertiser Reference Server ("ARS") 308. The ARS 308 is a system disposed on the network that is defined as the location to which data in the audio signal 111 is to be routed. As such, data in the audio signal 111 will always be routed to the ARS 308, since a URL is unique on the network system. Connected to the ARS 308 is a database 310 of product codes and associated manufacturer URLs. The database 310 undergoes a continual update process which is transparent to the user. As companies sign-on, e.g., subscribe, to this technology, manufacturer and product information is added to the database 310 without interrupting operation of the source PC 302 with frequent updates. When the advertiser server address URL is obtained from the ARS database 310, it and the request for the particular advertiser product information is automatically routed back through the web browser on PC 302, over to the respective advertiser server for retrieval of the advertiser product information to the PC 302. It should be noted that although the disclosed invention discusses a global communication network, the system is also applicable to LANs, WANs, and peer-to-peer network configurations. It should be noted that the disclosed architecture is not limited to a single source PC 302, but may comprise a plurality of source PCs, e.g., PC 300 and PC 303. Moreover, a plurality of ARS 308 systems and advertiser servers 312 may be implemented, e.g., ARS 314, and advertiser server A 316, respectively.

The information transactions, in general, which occur between the networked systems of this embodiment, over the communication network, are the following. The web browser running on source PC 302 transmits a message packet to the ARS 308 over Path "A." The ARS 308 decodes the message packet and performs a cross-reference function with product information extracted from the received message packet to obtain the address of an advertiser server 312. A new message packet is assembled comprising the advertiser server 312 address, and sent back to the source PC 302 over Path "B." A "handoff" operation is performed whereby the source PC 302 browser simply reroutes the information on to the advertiser server 312 over Path "C," with the appropriate source and destination address appended. The advertiser server 312 receives and

5 decodes the message packet. The request-for-advertiser-product-information is extracted and the
advertiser 312 retrieves the requested information from its database for transmission back to the
source PC 302 over Path "D." The source PC 302 then processes the information, i.e., for
10 display to the viewer. The optional Path "E" is discussed hereinbelow. It should be noted that
5 the disclosed methods are not limited to only browser communication applications, but may
accommodate, with sufficient modifications by one skilled in the art, other communication
15 applications used to transmit information over the Internet or communication network.

Referring now to FIGURE 4a, the message packet 400 sent from the source PC 302 to
ARS 308 via Path "A" comprises several fields. One field comprises the URL of the ARS 308
20 which indicates where the message packet is to be sent. Another field comprises the advertiser
product code or other information derived from the audio signal 111, and any additional overhead
information required for a given transaction. The product code provides a link to the address of
25 the advertiser server 312, located in the database 310. Yet another field comprises the network
address of the source PC 302. In general, network transmissions are effected in packets of
15 information, each packet providing a destination address, a source address, and data. These
packets vary depending upon the network transmission protocol utilized for communication.
30 Although the protocols utilized in the disclosed embodiment are of a conventional protocol suite
commonly known as TCP/IP, it should be understood that any protocols providing the similar
basic functions can be used, with the primary requirement that a browser can forward the routing
35 20 information to the desired URL in response to keystrokes being input to a PC. However, it
should be understood that any protocol can be used, with the primary requirement that a browser
can forward the product information to the desired URL in response to keystrokes being input to
40 a PC. Within the context of this disclosure, "message packet" shall refer to and comprise the
destination URL, product information, and source address, even though more than a single packet
25 must be transmitted to effect such a transmission.

45 Upon receipt of the message packet 400 from source PC 302, ARS 308 processes the
information in accordance with instructions embedded in the overhead information. The ARS
308 specifically will extract the product code information from the received packet 400 and, once
50 extracted, will then decode this product code information. Once decoded, this information is then
30 compared with data contained within the ARS advertiser database 310 to determine if there is a

5 "hit." If there is no "hit" indicating a match, then information is returned to the browser
indicating such. If there is a "hit," a packet 402 is assembled which comprises the address of the
source PC 302, and information instructing the source PC 302 as to how to access, directly in a
10 "handoff" operation, another location on the network, that of an advertiser server 312. This type
5 of construction is relatively conventional with browsers such as *Netscape®* and *Microsoft
Internet Explorer®* and, rather than displaying information from the ARS 308, the source PC 302
15 can then access the advertiser server 312. The ARS 308 transmits the packet 402 back to source
PC 302 over Path "B." Referring now to FIGURE 4b, the message packet 402 comprises the
address of the source PC 302, the URL of the advertiser server 312 embedded within
20 instructional code, and the URL of the ARS 308.

Upon receipt of the message packet 402 by the source PC 302, the message packet 402 is
disassembled to obtain pertinent routing information for assembly of a new message packet 404.
25 The web browser running on source PC 302 is now directed to obtain, over Path "C," the product
information relevant to the particular advertiser server 312 location information embedded in
15 message packet 404. Referring now to FIGURE 4c, the message packet 404 for this transaction
comprises the URL of the advertiser server 312, the request-for-product-information data, and the
30 address of the source PC 302.

Upon receipt of the message packet 404 from source PC 302, advertiser server 312
35 disassembles the message packet 404 to obtain the request-for-product-information data. The
advertiser server 312 then retrieves the particular product information from its database, and
20 transmits it over Path "D" back to the source PC 302. Referring now to FIGURE 4d, the
message packet 406 for this particular transaction comprises the address of the source PC 302,
40 the requested information, and the URL of the advertiser server 312.

Optionally, the ARS 308 may make a direct request for product information over Path
45 "E" to advertiser server 312. In this mode, the ARS 308 sends information to the advertiser
server 312 instructing it to contact the source PC 302. This, however, is unconventional and
requires more complex software control. The message packet 408 for this transaction is
50 illustrated in FIGURE 4e, which comprises the URL of the advertiser server 312, the request-for-
product-information data, and the address of the source PC 302. Since product information is not

5 being returned to the ARS 308, but directly to the source PC 302, the message packet 408 requires the return address to be that of the source PC 302. The product information is then
10 passed directly to PC 302 over Path "D."

Referring now to FIGURE 5, the method for detecting and obtaining product information
5 is as follows. In decision block 500, a proprietary application running resident on a source computer PC 302 (similar to PC 204) monitors the audio input for a special trigger signal. Upon
15 detection of the trigger signal, data following the trigger signal is decoded for further processing, in function block 502. In function block 504, the data is buffered for further manipulation. In decision block 506, a determination is made as to whether the data can be properly authenticated.
20 If not, program flow continues through the "N" signal to function block 520 where the data is discarded. In function block 522, the program then signals for a retransmission of the data. The system then waits for the next trigger signal, in decision block 500. If properly authenticated in
25 decision block 506, program flow continues through the "Y" signal path where the data is then used to launch the web browser application, as indicated in function block 508. In function block
15 510, the web browser receives the URL data, which is then automatically routed through the computer modem 208 to the network interface 304 and ultimately to the network 306. In
30 function block 514, the ARS 308 responds by returning the URL of advertiser server 312 to the PC 302. In function block 516, the web browser running on the source PC 302, receives the advertiser URL information from the ARS 308, and transmits the URL for the product file to the
35 20 advertiser server 312. In block 518, the advertiser server 312 responds by sending the product information to the source PC 302 for processing.

40 The user may obtain the benefits of this architecture by simply downloading the proprietary software over the network. Other methods for obtaining the software are well-known; for example, by CD, diskette, or pre-loaded hard drives.

45 25 Referring now to FIGURE 6, there is illustrated a flowchart of the process the ARS 308 may undergo when receiving the message packet 400 from the source PC 302. In decision block 600, the ARS 308 checks for the receipt of the message packet 400. If a message packet 400 is
50 not received, program flow moves along the "N" path to continue waiting for the message. If the message packet 400 is received, program flow continues along path "Y" for message processing.

5 Upon receipt of the message packet 400, in function block 602, the ARS 308 decodes the
message packet 400. The product code is then extracted independently in function block 604 in
preparation for matching the product code with the appropriate advertiser server address located
10 in the database 310. In function block 606, the product code is then used with a look-up table to
retrieve the advertiser server 312 URL of the respective product information contained in the
audio signal data. In function block 608, the ARS 308 then assembles message packet 402 for
15 transmission back to the source PC 302. Function block 610 indicates the process of sending the
message packet 402 back to the source PC 302 over Path "B."

Referring now to FIGURE 7, there is illustrated a flowchart of the interactive processes
20 between the source PC 302 and the advertiser server 312. In function block 700, the source PC
302 receives the message packet 402 back from the ARS 308 and begins to decode the packet
402. In function block 702, the URL of the advertiser product information is extracted from the
25 message packet 402 and saved for insertion into the message packet 404 to the advertiser server
312. The message packet 404 is then assembled and sent by the source PC 302 over Path "C" to
15 the advertiser server 312, in function block 704. While the source PC 302 waits, in function block
706, the advertiser server 312 receives the message packet 404 from the source PC 302, in
30 function block 708, and disassembles it. The product information location is then extracted from
the message packet 404 in function block 710. The particular product information is retrieved
from the advertiser server 312 database for transmission back to the source PC 302. In function
35 block 712, the product information is assembled into message packet 406 and then transmitted
back to the source PC 302 over Path "D." Returning to the source PC 302 in function block 714,
the advertiser product information contained in the message packet 406 received from the
40 advertiser server 312, is then extracted and processed in function block 716.

Referring now to FIGURE 8, after receipt of a trigger signal, a web browser application
25 on a source PC 302 is automatically launched and computer display 800 presents a browser page
802. Proprietary software running on the source PC 302 processes the audio signal data after
45 being digitized through the sound card 206. The software appropriately prepares the data for
insertion directly into the web browser by extracting the product information code and appending
keystroke data to this information. First, a URL page 804 is opened in response to a Ctrl-O
50 command added by the proprietary software as the first character string. Opening URL page 804
30

5 automatically positions the cursor in a field 806 where additional keystroke data following the
Ctrl-O command will be inserted. After URL page 804 is opened, the hypertext protocol
10 preamble http:// is inserted into the field 806. Next, URL information associated with the
location of the ARS 308 is inserted into field 806. Following the ARS 308 URL data are the
5 characters /? to allow entry of variables immediately following the /? characters. In this
embodiment, the variable following is the product information code received in the audio signal.
15 The product code information also provides the cross-reference information for obtaining the
advertiser URL from the ARS database 310. Next, a carriage return is added to send the
URL/product data and close the window 804. After the message packet 400 is transmitted to the
10 ARS 308 from the source PC 302, transactions from the ARS308, to the source PC 302, to the
20 advertiser server 312, and back to the source PC 302, occur quickly and are transparent to the
viewer. At this point, the next information the viewer sees is the product information which was
received from the advertiser server 312.

25 Referring now to FIGURE 9, there is illustrated a block diagram of a more simplified
15 embodiment. In this embodiment, a video source 902 is provided which is operable to provide an
audio output on an audio cable 901 which provides routing information referred to by reference
30 numeral 904. The routing information 904 is basically information contained within the audio
signal. This is an encoded or embedded signal. The important aspect of the routing information
904 is that it is automatically output in realtime as a function of the broadcast of the video
35 20 program received over the video source 902. Therefore, whenever the program is being
broadcast in realtime to the user 908, the routing information 904 will be output whenever the
producer of the video desires it to be produced. It should be understood that the box 902
40 representing the video source could be any type of media that will result in the routing
information being output. This could be a cassette player, a DVD player, an audio cassette, a CD
25 ROM or any such media. It is only important that this is a program that the producer develops
which the user 908 watches in a continuous or a streaming manner. Embedded within that
45 program, at a desired point selected by the producer, the routing information 904 is output.

50 The audio information is then routed to a PC 906, which is similar to the PC 112 in
FIGURE 1. A user 908 is interfaced with the PC to receive information thereof, the PC 906
30 having associated therewith a display (not shown). The PC 906 is interfaced with a network 910,

5 similar to the network 306 in FIGURE 3. This network 910 has multiple nodes thereon, one of
which is the PC 906, and another of which is represented by a network node 912 which
represents remote information. The object of the present embodiment is to access remote
10 information for display to the user 908 by the act of transmitting from the video program in block
5 902 the routing information 904. This routing information 904 is utilized to allow the PC 906
which has a network "browser" running thereon to "fetch" the remote information at the node
15 912 over the network 910 for display to the user 908. This routing information 904 is in the form
of an embedded code within the audio signal, as was described hereinabove.

20 Referring now to FIGURE 10, there is illustrated a more detailed block diagram of the
10 embodiment of FIGURE 9. In this embodiment, the PC 906 is split up into a couple of nodes, a
first PC 1002 and a second PC 1004. The PC 1002 resides at the node associated with the user
908, and the PC 1004 resides at another node. The PC 1004 represents the ARS 308 of FIGURE
25 3. The PC 1004 has a database 1006 associated therewith, which is basically the advertiser
database 310. Therefore, there are three nodes on the network 910 necessary to implement the
15 disclosed embodiment, the PC 1002, the PC 1004 and the remote information node 912. The
routing information 904 is utilized by the PC 1002 for routing to the PC 1004 to determine the
30 location of the remote information node 912 on the network 910. This is returned to the PC 1002
and a connection made directly with the remote information node 912 and the information
retrieved therefrom to the user 908. The routing information 904 basically constitutes primary
35 20 routing information.

40 Referring now to FIGURE 11, there is illustrated a diagrammatic view of how the
network packet is formed for sending the primary routing information to the PC 1004. In
general, the primary routing information occupies a single field which primary routing
information is then assembled into a data packet with the secondary routing information for
25 transfer to the network 910. This is described hereinabove in detail.

50 Referring now to FIGURE 12, there is illustrated an alternate embodiment to that of
FIGURE 9. In this embodiment, the video source 902 has associated therewith an optical region
1202, which optical region 1202 has disposed therein an embedded video code. This embedded
55

5 video code could be relatively complex or as simple as a grid of dark and white regions, each region in the grid able to have a dark color for a logic "1" or a white region for a logic "0." This will allow a digital value to be disposed within the optical region 1202. A sensor 1204 can then
10 be provided for sensing this video code. In the example above, this would merely require an array of optical detectors, one for each region in the grid to determine whether this is a logic "1" or a logic "0" state. One of the sensed video is then output to the PC 906 for processing thereof to determine the information contained therein, which information contained therein constitutes the primary routing information 904. Thereafter, it is processed as described hereinabove with reference to FIGURE 9.

10 Referring now to FIGURE 13, there is illustrated a block diagram for an embodiment wherein a user's profile can be forwarded to the original subscriber or manufacturer. The PC 906 has associated therewith a profile database 1302, which profile database 1302 is operable to store
25 a profile of the user 908. This profile is created when the program, after initial installation, requests profile information to be input in order to activate the program. In addition to the profile, there is also a unique ID that is provided to the user 908 in association with the browser program that runs on the PC 906. This is stored in a storage location represented by a block
30 1304. This ID 1304 is accessible by a remote location as a "cookie" which is information that is stored in the PC 906 in an accessible location, which accessible location is actually accessible by the remote program running on a remote node.

35 The ARS 308, which basically constitutes the PC 1004 of FIGURE 10, is operable to have associated therewith a profile database 1308, which profile database 1308 is operable to store profiles for all of the users. The profile database 1308 is a combination of the stored in
40 profile database 1302 for all of the PCs 906 that are attachable to the system. This is to be distinguished from information stored in the database 310, the advertiser's database, which contains intermediate destination tables. When the routing information in the primary routing information 904 is forwarded to the ARS 308 and extracted from the original data packet, the look-up procedure described hereinabove can then be performed to determine where this information is to be routed. The profile database 1302 is then utilized for each transaction,
45 wherein each transaction in the form of the routing information received from the primary routing information 904 is compared to the destination tables 310 to determine what manufacturer it is

5 associated with. The associated ID 1304 that is transmitted along with the routing information in
primary routing information 904 is then compared with the profile database 1308 to determine if
a profile associated therewith is available. This information is stored in a transaction database
10 1310 such that, at a later time, for each routing code received in the form of the information in
5 primary routing information 904, there will associated therewith the IDs 1304 of each of the PCs
906. The associated profiles in database 1308, which are stored in association with IDs 1304, can
then be assembled and transmitted to a subscriber as referenced by a subscriber node 1312 on the
15 network 910. The ARS 308 can do this in two modes, a realtime mode or a non-realtime mode.
In a realtime mode, each time a PC 906 accesses the advertiser database 310, that user's profile
information is uploaded to the subscriber node 1312. At the same time, billing information is
20 generated for that subscriber 1312 which is stored in a billing database 1316. Therefore, the ARS
308 has the ability to inform the subscriber 1312 of each transaction, bill for those transactions,
and also provide to the subscriber 1312 profile information regarding who is accessing the
25 particular product advertisement having associated therewith the routing information field 904
for a particular routing code as described hereinabove. This information, once assembled, can
then be transmitted to the subscriber 1312 and also be reflected in billing information and stored
30 in the billing information database 1316.

Referring now to FIGURE 14, there is illustrated a flowchart depicting the operation for
storing the profile for the user. The program is initiated in a block 1402 and then proceeds to a
35 20 function block 1404, wherein the system will prompt for the profile upon initiation of the system.
This initiation is a function that is set to activate whenever the user initially loads the software
that he or she is provided. The purpose for this is to create, in addition to the setup information, a
40 user profile. Once the user is prompted for this, then the program will flow to a decision block
1406 to determine whether the user provides basic or detailed information. This is selectable by
25 the user. If selecting basic, the program will flow to a function block 1408 wherein the user will
enter basic information such as name and serial number and possibly an address. However, to
45 provide some incentive to the user to enter more information, the original prompt in function
block 1404 would have offers for such things as coupons, discounts, etc, if the user will enter
additional information. If the user selects this option, the program from the decision block 1406
50 30 to a function block 1410. In the function block 1410, the user is prompted to enter specific

5 information such as job, income level, general family history, demographic information and more. There can be any amount of information collected in this particular function block.

10 Once all of the information is collected, in either the basic mode or the more specific mode, the program will then flow to a function block 1412 where this information is stored
5 locally. The program then flows to a decision block 1414 to then go on-line to the host or the ARS 308. In general, the user is prompted to determine whether he or she wants to send this
15 information to the host at the present time or to send it later. If he or she selects the "later" option, the program will flow to a function block 1415 to prompt the user at a later time to send the information. In the disclosed embodiment, the user will not be able to utilize the software
20 until the profile information is sent to the host. Therefore, the user may have to activate this at a later time in order to connect with the host.

25 If the user has selected the option to upload the profile information to the host, the program will flow to the function block 1416 to initiate the connect process and then to a decision block 1418 to determine if the connection has been made. If not, the program will flow
15 along a "N" path to a time to decision block 1420 which will time to an error block 1422 or back to the input of the connect decision block 1418. The program, once connected, will then flow
30 along a "Y" path from decision block 1418 to a function block 1428 to send the profile information with the ID of the computer or user to the host. The ID is basically, as described
35 hereinabove, a "cookie" in the computer which is accessed by the program when transmitting to the host. The program will then flow to a function block 1430 to activate the program such that
20 it, at later time, can operate without requiring all of the set up information. In general, all of the operation of this flowchart is performed with a "wizard" which steps the user through the setup
40 process. Once complete, the program will flow to a Done block 1432.

45 Referring now to FIGURE 15, there is illustrated a flowchart depicting the operation of the host when receiving a transaction. The program is initiated at a start block 1502 and then
25 proceeds to decision block 1504, wherein it is determined whether the system has received a routing request, i.e., the routing information 904 in the form of a tone, etc., embedded in the
50 audio signal as described hereinabove with respect to FIGURE 9. The program will loop back around to the input of decision block 1504 until the routing request has been received. At this

5

10

15

20

25

time, the program will flow along the "Y" path to a function block 1506 to receive the primary routing information and the user ID. Essentially, this primary routing information is extracted from the audio tone, in addition to the user ID. The program then flows to a function block 1508 to look up the manufacturer URL that corresponds to the received primary routing information and then return the necessary command information to the originating PC 108 in order to allow that PC to connect to the destination associated with the primary routing information. Thereafter, the program will flow to a function block 1510 to update the transaction database 1310 for the current transaction. In general, the routing information 904 will be stored as a single field with the associated IDs. The profile database, as described hereinabove, has associated therewith detailed profiles of each user on the system that has activated their software in association with their ID. Since the ID was sent in association with the routing information, what is stored in the transaction database is the routing code, in association with all of the IDs transmitted to the system in association with that particular routing code. Once this transaction database has been updated, as described hereinabove, the transactions can be transferred back to the subscriber at node 312 with the detailed profile information from the profile database 1308.

30

35

40

The profile information can be transmitted back to the subscriber or manufacturer in the node 312 in realtime or non-realtime. A decision block 1512 is provided for this, which determines if the delivery is realtime. If realtime, the program will flow along a "Y" path to a function block 1514 wherein the information will be immediately forwarded to the manufacturer or subscriber. The program will then flow to a function block 1516 wherein the billing for that particular manufacturer or subscriber will be updated in the billing database 1316. The program will then flow into an End block 1518. If it was non-realtime, the program moves along the "N" path to a function block 1520 wherein it is set for a later delivery and it is accrued in the transaction database. In any event, the transaction database will accrue all information associated with a particular routing code.

45

50

With a realtime transaction, it is possible for a manufacturer to place an ad in a magazine or to place a product on a shelf at a particular time. The manufacturer can thereafter monitor the times when either the ads are or the products are purchased. Of course, they must be scanned into a computer which will provide some delay. However, the manufacturer can gain a very current view of how a product is moving. For example, if a cola manufacturer were to provide a

55

5 promotional advertisement on, for example, television, indicating that a new cola was going to be
placed on the shelf and that the first 1000 purchasers, for example, scanning their code into the
10 network would receive some benefit, such as a chance to win a trip to some famous resort in
Florida or some other incentive, the manufacturer would have a very good idea as to how well the
5 advertisement was received. Further, the advertiser would know where the receptive markets
were. If this advertiser, for example, had placed the television advertisement in ten cities and
15 received overwhelming response from one city, but very poor response from another city, he
would then have some inclination to believe that either one poor response city was not a good
market or that the advertising medium he had chosen was very poor. Since the advertiser can
10 obtain a relatively instant response and also content with that response as to the demographics of
the responder, very important information can be obtained in a relatively short time.

25 It should be noted that the disclosed embodiment is not limited to a single source PC 302,
but may encompass a large number of source computers connected over a global communication
15 network. Additionally, the embodiment is not limited to a single ARS 308 or a single advertiser
server 312, but may include a plurality of ARS and advertiser systems, indicated by the addition
of ARS 314 and advertiser server A 316, respectively. It should also be noted that this
30 embodiment is not limited only to global communication networks, but also may be used with
LAN, WAN, and peer-to-peer configurations.

35 20 It should also be noted that the disclosed embodiment is not limited to a personal
computer, but is also applicable to, for example, a Network Computer ("NctPC"), a scaled-down
version of the PC, or any system which accommodates user interaction and interfaces to
40 information resources.

25 One typical application of the above noted technique is for providing a triggering event
during a program, such as a sport event. In a first example, this may be generated by an
45 advertiser. One could imagine that, due to the cost of advertisements in a high profile sports
program, there is a desire to utilize this time widely. If, for example, an advertiser contracted for
15 seconds worth of advertising time, they could insert within their program a tone containing the
50 30 routing information. This routing information can then be output to the user's PC which will
cause the user's PC to, via the network, obtain information from a remote location typically

5 controlled by the advertiser. This could be in the form of an advertisement of a length longer
than that contracted for. Further, this could be an interactive type of advertisement. An
important aspect to the type of interaction between the actual broadcast program with the
10 embedded routing information and the manufacturer's site is the fact that there is provided in the
5 information as to the user's PC and a profile of the user themselves. Therefore, an advertiser can
actually gain realtime information as to the number of individuals that are watching their
15 particular advertisement and also information as to the background of those individuals,
demographic information, etc. This can be a very valuable asset to an advertiser.

20 In another example, the producer of the program, whether it be an on-air program, a
10 program embedded in a video tape, CD-ROM, DVD, or a cassette, can allow the user to
automatically access additional information that is not displayed on the screen. For example, in a
sporting event, various statistics can be provided to the user from a remote location, merely by
25 the viewer watching the program. When these statistics are provided, the advertiser can be
provided with demographic information and background information regarding the user. This
15 can be important when, for example, the user may record a sports program. If the manufacturer
sees that this program routing code is being output from some device at a later time than the
30 actual broadcast itself, this allows the advertisers to actually see that their program is still being
used and also what type of individual is using it. Alternatively, the broadcaster could determine
the same and actually bill the advertiser an additional sum for a later broadcast. This is all due to
35 20 the fact that the routing information automatically, through a PC and a network, will provide an
indication to the advertiser for other intermediary regarding the time at which the actual
information was broadcast.

40 The different type of medium that can be utilized with the above embodiment are such
things as advertisements, which are discussed hereinabove, contests, games, news programs,
25 education, coupon promotional programs, demonstration media (demos), photographs, all of
45 which can be broadcast on a private site or a public site. This all will provide the ability to allow
realtime interface with the network and the remote location for obtaining the routed information
and also allow for realtime billing and accounting.

50

55

5

Although the preferred embodiment has been described in detail, it should be understood that various changes, substitutions and alterations can be made therein without departing from the spirit and scope of the invention as defined by the appended claims.

10

15

20

25

30

35

40

45

50

55

THIS PAGE BLANK (USPTO)

Claims

5

10

15

20

25

30

35

40

45

50

55

5

WHAT IS CLAIMED IS:

10

1. A method for controlling a computer, comprising the steps of:
inputting an analog signal at a source location on a network, said analog signal
comprising a product identifier which is in close association with a product such that it identifies
the associated product;
appending routing information to the product identifier, which routing information
defines the location of a remote location on the network; and
transmitting the product identifier from the source location to the remote location
over the network in accordance with the appended routing information, which routing
information defines the network connection between the source location and the remote location
on the network, wherein information regarding the associated product can be returned to the
source location from the remote location.

25

2. The method of Claim 1, wherein the step of transmitting the product information
is performed in response to the step of inputting.

30

3. The method of Claim 1, wherein the step of appending the routing information
occurs in response to the step of inputting.

35

4. The method of Claim 1, wherein the analog signal is input to a sound card.

40

45

50

55

5

10

15

20

25

30

35

40

45

50

55

5. The method of Claim 1, wherein the routing information is associated with a secondary location on the network such that the step of transmitting to the remote location transmits the product identifier to the remote location in association with routing information, for returning to the source location, and further comprising:

accessing a database of product routing information which provides an association between a predetermined product identifier and a remote product information location on the network, there being a plurality of such product routing information stored in the database;

accessing the database in response to receiving at the secondary location a transmitted product identifier from the source location;

comparing the received product identifier with the stored product routing information in the database;

if there is a match between the received product identifier and any of the stored product routing information, transmitting the matching product routing information back to the source location; and

at the source location, in response to receiving the matching product routing information, interconnecting the source location with the product information location over the network and receiving product information therefrom.

6. The method of Claim 5, and further comprising the step of displaying the received product information.

7. The method of Claim 1, wherein the network is a global communication network that provides a universal resource locator (URL) for each location on the network and the routing information is comprised of the URL for the location.

8. The method of Claim 7, wherein a processing system is provided running a program that receives input in the form of keystrokes for routing of information thereto, and the step of appending routing information comprises the step of forming a keystroke string that emulates the combination of the routing information and the product identifier in keystrokes and transmits the emulated keystrokes to the program in the same manner that a user would key the strokes in, and the step of transmitting is performed in response to the appended routing information and product identifier transmitted to the program with an appended command

5

associated therewith that instructs the program to perform a transmit operation in a manner similar to a user interacting with the program to transmit routing information.

10

9. The method of Claim 8, wherein the appended routing information includes instructional information as to how the remote location is to handle the transmitted product identifier.

15

10. The method of Claim 9, wherein the program is a web browser which is automatically launched in response to said analog signal.

20

25

30

35

40

45

50

55

5

11. A method for retrieving information from a storage region having a defined location, comprising the steps of:

10

broadcasting a program having embedded therein a routing signal having routing information contained therein;

5

extracting the routing signal from the broadcast; and

15

controlling a personal computer for a user to retrieve the information from a storage region at the defined location, which defined location is located with the extracted routing information, providing it at the personal computer for use by the user.

20

12. The method of Claim 11, wherein the personal computer has a display associated therewith, wherein the retrieved information is displayed on the display.

25

13. The method of Claim 11, wherein the broadcast program is a video program.

14. The method of Claim 11, wherein the broadcast program is an audio program.

30

15. The method of Claim 11, wherein the routing signal comprises an audio signal and wherein the step of extracting comprises decoding the information in the audio signal by the personal computer.

35

16. The method of Claim 15, wherein the broadcast program is a video program.

17. The method of Claim 15, wherein the broadcast program is an audio program.

40

18. The method of Claim 15, wherein the step of extracting routing information comprises connecting the video source to the personal computer with a cable which carries only audio information, the personal computer then decoding from the audio information in the step of extracting the routing information from the routing signal.

45

50

19. The method of Claim 11, wherein the routing signal is a video signal and the broadcast program is a video program and the step of extracting comprises extracting the embedded video information from the video routing signal.

55

5

20. The method of Claim 11, wherein the storage region is disposed on a remote location on a network, and the step of controlling comprises:

10

transferring the routing information to an intermediate node on the network;

5

storing at the intermediate node on the network lookup information defining the location of the storage region on the network correlated with the routing information, such that a unique routing information is associated with a particular storage region on the network;

15

looking up at the intermediate node the correlated location of the storage region returning the location information to the personal computer;

20

accessing the information from the location information retrieved from the intermediate node and the storage base associated therewith and retrieving the information therefrom for delivery to the personal computer and for use by the user.

25

21. The method of Claim 20 and further comprising the step of storing at a desired location profile information associated with the user and storing at the personal computer identification information as associated with the profile information at the desired location and further comprising the step of transmitting the identification information to the intermediate node when transmitting the routing information thereto, which identification information can be stored thereat for later association with the stored profile information at the desired location.

30

35

22. The method of Claim 21, and further comprising the step of transmitting profile information from the desired location to a remote subscriber location which remote subscriber location is associated with the routing information, such that profile information is transmitted to the routing information from the user and the associated identification signals that is associated with the extracted routing information from the broadcast.




40

45

23. The method of Claim 22, wherein the identification signals are accumulated for each routing signal transmitted from different locations on the network and different personal locations on the network and different personal computers which can be transmitted to the subscriber location at a later time.

50

55



PATH A: SOURCE TO ARS



FIG. 4a

PATH B: ARS TO SOURCE



FIG. 4b

PATH C: SOURCE TO ADVERTISER



FIG. 4c

PATH D: ADVERTISER TO SOURCE




FIG. 4d

PATH E: ARS TO ADVERTISER (OPTIONAL)




FIG. 4e




FIG. 6




FIG. 5









FIG. 7



OPEN PAGE
 USE HYPERTEXT PROTOCOL
 URL OF ADS
 ALLOW VARIABLE APPENDING
 APPENDED VARIABLE (e.g., UPC CODE)
 CARRIAGE RETURN - TRANSMIT DATA








FIG. 14




FIG. 15

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US99/20963

A. CLASSIFICATION OF SUBJECT MATTER IPC(6) : G06F 13/00, 15/16 US CL : 709/238, 239, 249 According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) U.S. : 709/238, 239, 249, 218, 234; 345/327 Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched Electronic data base consulted during the international search (name of data base and, where practicable, search terms used) WEST, EAST		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X,P	US 5,854,897 A (RADZIEWICZ et al) 29 December 1998, col. 7, lines 18-67, col. 9, line 64 - col. 10, line 52, col. 11, lines 6-29, col. 12, lines 23-45.	1-23
A	US 5,774,664 A (HIDARY et al) 30 June 1998, col. 2, line 33 - col. 3, line 18, col. 4, lines 28-39.	1-23
A,P	US 5,929,850 A (BROADWIN et al) 27 July 1999, col. 1, lines 31-58, col. 4, line 65 - col. 5, line 8, lines 34-42, col. 17, line 61 - col. 18, line 55.	1-23
A,E	US 5,974,451 A (SIMMONS) 26 October 1999, col. line 27 - col. 2, line 10, col. 7, lines 6-65.	1-3, 11, 20-23
<input type="checkbox"/> Further documents are listed in the continuation of Box C. <input type="checkbox"/> See patent family annex.		
* Special categories of cited documents: "A" document defining the general state of the art which is not considered to be of particular relevance "B" earlier document published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed		"I" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "A" document member of the same patent family
Date of the actual completion of the international search 20 NOVEMBER 1999		Date of mailing of the international search report 06 DEC 1999
Name and mailing address of the ISA/US Commissioner of Patents and Trademarks Box PCT Washington, D.C. 20231 Facsimile No. (703) 305-3230		Authorized officer FRANK J ASTA <i>James R. Matthews</i> Telephone No. (703) 305-3817

THIS PAGE BLANK (USPTO)